

Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318 (952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121 Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem

Material Safety Data Sheet GREENchoice Smoke & Gci bX'GYUUbh

1. Product and company identification

CAS # : mixture

Address : Franklin International

2020 Bruck Street Columbus OH 43207

Contact person : Franklin Technical Services

Telephone : (800) 877-4583 **In case of emergency** : Franklin Security (614) 445-1300

Reference number : 8001
Product code : 2892
Date of revision : 3/25/2013.
Print date : 3/25/2013.

 Chemtrec (24 Hour)
 : (800) 424 - 9300

 Chemtrec International
 : (703) 527 - 3887

Product use : Caulk

Acrylic latex

2. Hazards identification

Emergency overview

Physical state : Liquid. [Paste.]

Color : White.

Odor : Characteristic.
Signal word : CAUTION!

Hazard statements : MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Precautionary measures : Avoid breathing vapor or mist. Use only with adequate ventilation. Avoid contact with

eyes, skin and clothing. Keep container tightly closed. Wash thoroughly after handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Routes of entry : Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system. Inhalation of oil mist or vapors at elevated

temperatures may cause respiratory irritation.

Ingestion : No known significant effects or critical hazards.

Skin : Slightly irritating to the skin. Prolonged or repeated contact can defat the skin and lead to

irritation, cracking and/or dermatitis.

Eyes: Moderately irritating to eyes. This product may irritate eyes upon contact.

Potential chronic health effects

Chronic effects
 No known significant effects or critical hazards.
 Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

3/25/2013. 2892 **1/10**

2. Hazards identification

Target organs: May cause damage to the following organs: skin, eyes.

Contains material which may cause damage to the following organs: kidneys, upper

respiratory tract, central nervous system (CNS), eye, lens or cornea.

Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : No specific data.

Skin : Adverse symptoms may include the following:

irritation redness

Eyes: Adverse symptoms may include the following:

irritation watering redness

Medical conditions aggravated by over-exposure

None known.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
Solvent naphtha (petroleum), medium aliph.	64742-88-7	1 - 5

<u>Canada</u>

Name	CAS number	%
Solvent naphtha (petroleum), medium aliph. ethanediol	64742-88-7 107-21-1	1 - 5 0.1 - 0.5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Small spill

: Stop leak if without risk. Move containers from spill area. Dispose of via a licensed waste disposal contractor. Absorb with an inert material.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store between the following temperatures: 5 to 38°C (41 to 100.4°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
Solvent naphtha (petroleum), medium aliph.	OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hour(s). TWA: 400 mg/m³ 8 hour(s). OSHA PEL (United States, 6/2010). TWA: 100 ppm 8 hour(s). TWA: 400 mg/m³ 8 hour(s).

8. Exposure controls/personal protection

Canada

Occupational exposure limits		TWA (8 hours)		STEL (15 mins)		Ceiling					
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
ethanediol	US ACGIH 3/2012 AB 4/2009 BC 4/2012 ON 7/2010 QC 9/2011	- - - - -	- - 10 - -	- - - - -	- - - - - - 50	- - 20 - - 127	-	- - - - 50 -	100 100 100 - - 100	-	[a] [3] [b] [a] [c] [d] [b] [e]

[3]Skin sensitization

Form: [a]Aerosol [b]aerosol [c]Particulate [d]Vapour [e]vapour and mist

Mexico

Occupational exposure limits

No exposure limit value known.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes

 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

Physical state : Liquid. [Paste.]

Flash point : Closed cup: >93.333°C (>200°F) [Setaflash.]

Color : White.

Odor : Characteristic.

pH : 7 to 8

Boiling/condensation point : 100°C (212°F) **Relative density** : 1.52423 **Volatility** : 19.14% (w/w)

3/25/2013. 2892 **4/10**

9. Physical and chemical properties

Evaporation rate : >1 (butyl acetate = 1)

VOC (less water, less exempt solvents)

: 40.82 g/l

10. Stability and reactivity

Chemical stability : The product is stable.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products

 Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous

: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions
Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

Incompatibility: Reactive or incompatible with the following materials: acids and alkalis.

11. Toxicological information

United States

Acute toxicity

No known significant effects or critical hazards.

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Conclusion/Summary

Skin : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Eyes : This product may irritate eyes upon contact.

Respiratory: Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.

Sensitizer

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Canada

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanediol	LD50 Oral	Rat	4700 mg/kg	-

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation

11. Toxicological information

ethanediol	Eyes - Mild irritant	Rabbit	-	24 hours 500 -	
				milligrams	
	Eyes - Mild irritant	Rabbit	-	1 hours 100 -	
	j			milligrams	
	Eyes - Moderate irritant	Rabbit	-	6 hours 1440 -	
	,			milligrams	
	Skin - Mild irritant	Rabbit	L	555 -	
	Okin Willa Irritarit	rabbit		milligrams	
				riningrariis	

Conclusion/Summary

Skin : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Eyes: This product may irritate eyes upon contact.

Respiratory: Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.

Sensitizer

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

Mexico

Acute toxicity

No known significant effects or critical hazards.

Chronic toxicity

No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Not available.					

Conclusion/Summary

Skin: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Eyes : This product may irritate eyes upon contact.

Respiratory: Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.

<u>Sensitizer</u>

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Reproductive toxicity

No known significant effects or critical hazards.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

3/25/2013. 2892 **6/10**

12. Ecological information

United States

Aquatic ecotoxicity

No known significant effects or critical hazards.

Persistence/degradability

No known significant effects or critical hazards.

Canada

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
ethanediol	Acute LC50 100000 ug/L Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 10000000 ug/L Fresh water Acute LC50 8050000 ug/L Fresh water	Daphnia - Daphnia magna Fish - Pimephales promelas - <=7 days	48 hours 96 hours

Persistence/degradability

No known significant effects or critical hazards.

Mexico

Aquatic ecotoxicity

No known significant effects or critical hazards.

Persistence/degradability

No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory	UN number	Proper shipping	Classes	PG*	Label	Additional
information	ON Humber	name	Classes	FG	Label	information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	Not regulated.	-	-	-		-
Mexico Classification	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
	1					i

14. Transport information **IATA-DGR Class** Not regulated.

PG*: Packing group

15. Regulatory information

United States

HCS Classification : Irritating material

U.S. Federal regulations

: TSCA 4(a) final test rules: sodium hydroxymethanesulphinate

TSCA 8(a) PAIR: Nonylphenol, branched, ethoxylated; meguinol; Poly(oxy-1,2-

ethanediyl), α -[(1,1,3,3-tetramethylbutyl)phenyl]- ω -hydroxy-TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Solvent naphtha (petroleum), medium

SARA 311/312 MSDS distribution - chemical inventory - hazard identification:

GREENchoice Smoke & Sound Sealant: Immediate (acute) health hazard

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

Class I Substances

Clean Air Act Section 602 : Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

: Not listed

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals)

: Not listed

State regulations

Massachusetts : None of the components are listed.

New York : None of the components are listed. **New Jersey** : None of the components are listed. **Pennsylvania** : None of the components are listed.

Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

Canadian lists

Canadian NPRI : The following components are listed: Solvent naphtha medium aliphatic

CEPA Toxic substances : None of the components are listed.

Canada inventory Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification

15. Regulatory information



International regulations

International lists : Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined.

Japan inventory: Not determined. **Korea inventory**: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Chemical Weapons

Convention List Schedule I

Chemicals

Chemical Weapons

Convention List Schedule

II Chemicals

Chemical Weapons

Convention List Schedule

III Chemicals

Not listed

: Not listed

: Not listed

16. Other information

Label requirements

: MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Hazardous Material

Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing : **3/25/2013. Date of issue** : 3/25/2013.

16. Other information

Date of previous issue : 1/16/2013.

Version : 2

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.