









SCALE: AS NOTED

123 Columbia Court North, Chaska, Minnesota 55318 P. 800.527.6253 LAST REVISED: 1/30/2020

DRAWN BY: BH

SCREW TYPE CHART			
PANEL THICKNESS	SUBSTRATE	RECOMMENDED SCREW TYPE	RECOMMENDED SCREW LENGTH
1"	DRYWALL OR PLYWOOD	DRYWALL SCREW	1-5/8"
1-3/8"	DRYWALL OR PLYWOOD	DRYWALL SCREW	2-1/4"
2"	DRYWALL OR PLYWOOD	DRYWALL SCREW	3"
1"	CONCRETE	TAPCON	2-1/4"
1-3/8"	CONCRETE	TAPCON	2-3/4"
2"	CONCRETE	TAPCON	3-1/4"

SCREW SPACING CHART				
APPLICATION	MINIMUM O.C. SPACING	MINIMUM SCREW DISTANCE FROM EDGE OF PANEL		
CEILING	12"	3'' 4		
WALL	24"	<u>3</u> 11 4		
WALL: HIGH TRAFFIC	12"	3" 4		

TTTTT TH

#6 SHARP POINT DRYWALL SCREW RECOMMENDED FOR WOOD APPLICATION

#6 CMU SCREW RECOMMENDED FOR MASONRY APPLICATION

#6 SELF TAPPING SCREW RECOMMENDED FOR METAL APPLICATIONS)



ENVIROCOUSTIC WOOD WOOL - SHAPES FASTENER OPTIONS (FOR MOUNTING OPTION 1) NOTES: ABOVE FASTENERS ARE RECOMMENDED BY ASI FOR DIRECT ATTACH APPLICATION -FASTENERS BY OTHER

SHEET NUMBER

SCALE: AS NOTED

LAST REVISED: 1/30/2020

DRAWN BY: BH